

ASPHALT REPAIR



Unit of measurement	Pieces/Pallet	Consumption	Color/other specifications
20 kg / bucket	36 pcs/pallet	250 ml/m ² /mm	Black



ASPHALT REPAIR

Cold asphalt for road repair.

FEATURES

Product is ready to be applied; it is cold bitumen-based for repairs of small holes in streets or sidewalks. It is characterized by high flexibility, does not create cracking due to its swelling coefficient. It has excellent adhesive properties and is not damaged by car tires. The product has high resistance to weather conditions and over time. It is easily workable and does not have specific request regarding the preparation of the substrate. Also, the surface becomes trafficable immediately.

AREA OF APPLICATION

Suitable for rapid restoration of (holes, cracks etc.) asphalt or sidewalks. Ideal for local repairs on highways, roads, bridges, parking lots and yards, industries, schools, hospitals etc.

MANNER OF APPLICATION

The support where Asphalt Repair will be applied should be cleaned in advance from dust and petroleum, oils, varnishes, wax residues, and anti-adhesive materials. Cleaning of oils, varnishes, wax or anti-adhesive materials is done mechanically or manually. For holes over 10 cm, it is recommended to fill the holes with inerts, to compress really well and then apply the product. Product application is made 1-2 cm above the hole level and then it is compressed with a roller.



TECHNICAL DATA (IN 23°C AND 50% RH)

Chemical base	Bitumen asphalt
Specific weight of mixture	2,10±0,05 kg/lit
Color	Black
Application temperature	-40°C to +60°C

PACKAGING

Bucket of 20 kg.

CONSUMPTION

20-22 kg/m² for cm thickness

SHELF LIFE - STORAGE

It is stored in its closed packaging, in dry, low-moisture and shady places, for at least 18 months after manufacture date.