


DECOQUARTZ



NAME	UNIT OF MEASUREMENT	PIECES/PALLET	CONSUMPTION	COLOR/ OTHER SPECIFICATIONS
1. Sahara 2. Canus 3. Canus Dark 4. Terra Nera 5. Smerald 6. Desert 7. Jasper 8. Lividus 9. Fulvus 10. Dark Sky 11. Firebrick 12. Snow 13. Brunt 14. River stone 15. Clay 16. Colorado	25 kg/bucket	27 pcs/pallet	5kg/m ²	White and ocher White and gray White, Grey, Black Black coffee Green and white Ocher and brown lightly Green and black Blue and black Brown and white Blue and gray Grayish red Little white ocher Ocher and white Black, white and yellow White, light gray and ocher Yellow, red



DECOQUARTZ

Decorative coating that serves for the treatment of facades and indoor surfaces.

PRODUCT CLASSIFICATION

DECOQUARTZ is classified according to EN 15824 standard.

FEATURES

- For indoor and outdoor use.
- High resistance to weather conditions.
- Good workability.
- Forms a stable and long-lasting structure.

AREA OF APPLICATION

DECOQUARTZ is suitable to create decorative coatings with excellent waterproof, adhesive and elastic qualities. It is also used to create decorative coatings on surfaces filled with cement mortar or basic thermal insulating mortar, which have been flattened beforehand with TECNOFIX or one product from DW CONEXION line of products.

PROCEDURE OF APPLICATION

Preparation of support:

The support where DECOQUARTZ will be applied should be beforehand cleaned from dust and petroleum, oils, varnishes and wax residues, and from anti-adhesion materials. The cleaning of oils, varnishes, wax or anti-adhesion materials is done mechanically or manually. Before the application of DECOQUARTZ, level the support with the dry primer TECNOFIX. Supports should be flat and mechanically stable, in function of intended use.

MANNER OF APPLICATION

DECOQUARTZ is applied through a straight, metallic screed directly on the surface which has been pre-treated with TECNOFIX LIQUID primer. After putting the product on the support, compress it with a plastic screed, to create the structures you wish.

PACKAGING

DECOQUARTZ is supplied in buckets of 25 kg.

SEHLF-LIFE STORAGE

24 months after manufacture date, if stored in original and unopened packaging and protected from direct exposure to sun and frost.

CONSUMPTION

5 kg for m²

TECHNICAL DATA

Form	Paste
Color	Various
Volumetric weight	1750 Kg/m ³
Application temperature	+5°C to +35°C

