

DW PVC ECO 110

Unit of measurement	Pieces/Pallet	Consumption	Color/Other specifications
5 kg/bucket	60 pcs/pallet	1-1.5 kg/m ²	Beige
15 kg/bucket	36 pcs/pallet		-



DW PVC ECO 110

Fast drying, water-based dispersion adhesive for the adhesion of PVC-s, solvents-free.

CHARACTERISTICS

- DW PVC ECO 110 is a synthetic, fast drying, water emulsion-based adhesive, free of VOC - s.
- DW PVC ECO 110 has a high adhesiveness, even from the early stages of application time.
- DW PVC ECO 110 reaches a high level of flexibility and adhesiveness.
- DW PVC ECO 110 ensures excellent adhesion in any type of support.

APPLICATION PROCEDURE

Preparation of the surface

Surface must be completely dry, absorbent, leveled, mechanically stable, and free of dust, loose particles, paint, wax, oil, rust, and traces of gypsum. Moisture content should be lower than the maximum specified by the manufacturers of parquet, 2-3% for cement-based floors and 0.5% for anhydrous- based floors. Check moisture throughout the thickness of the layer, by using a hygrometer. Floating layers on the isolations, facilitated layers and tiles should be equipped with a vapor barrier to prevent moisture condensation.

APPLICATION

Mix the adhesive before using it. If you see the formation of a superficial skin, remove it in any case. DW PVC ECO 110 is applied on surfaces through a notched trowel, suitable for parquets. Service life of DW PVC ECO 110 product is maximally 30 minutes in normal weather conditions and moisture level. If you see the creation of a skin during the application of DW PVC ECO 110, the adhesive is removed and re-applied. Environment temperature should be higher than +10°C.



TECHNICAL DATA

Form	Paste
Color	Beige
Density	1.30 Kg/L
Working life	30 minutes
The solid residue	65%

CONSUMPTION

Depending on the type of trowel:

600-800 g / m² by using a 4 mm-notch trowel.
800 - 1000 g / m² by using a 6 mm-notch trowel.

PACKAGING

DW PVC ECO 110 is supplied in buckets of 5 and 15 kg, in beige color.

SHELF-LIFE-STORAGE

12 months if stored in a cool environment, in its original and closed packaging.

