

DW RUBBER ECO 530

Unit of measurement	Pieces/Pallet	Consumption	Color/Other specifications
5 kg/bucket	60 pcs/pallet	1-1.5 kg/m ²	White
15 kg/bucket	36 pcs/pallet		-



DW RUBBER ECO 530

Adhesive for the mounting of rubber elements, with water-based dispersion and free of solvents.

CHARACTERISTICS

- DW RUBBER ECO 530 is a water-based emulsion adhesive, free of VOC-s.
- DW RUBBER ECO 530 ensures a high adhesion even in non-porous surfaces.
- DW RUBBER ECO 530 reaches a high level of flexibility and adhesive-ness.
- DW RUBBER ECO 530 is used for the adhesion of polystyrene panels on walls and ceilings.

APPLICATION PROCEDURE

Preparation of the surface

Surface must be completely dry, absorbent, leveled, mechanically stable, and free of dust, loose particles, paint, wax, oil, rust, and traces of gypsum. The moisture content should be lower than the maximum specified by the manufacturers of parquet, 2 - 3% for cement-based floors and 0.5% for anhydrous-based floors. Check moisture throughout the thickness of the layer, using a hydrometer. Floating layers on the insulations, facilitated layers and tiles should be equipped with a vapor barrier to prevent moisture condensation.

APPLICATION

Mix the adhesive before using it. If you see the formation of a superficial skin, remove it in any case. DW RUBBER ECO 530 is applied on surfaces through a notched trowel, suitable for parquets. Working time of DW RUBBER ECO 530 product is maximally 30 minutes in normal temperature and moisture conditions. If you see the creation of a skin during the application of DW RUBBER ECO 530, the adhesive is removed and re-applied. Environment temperature should be higher than +10°C.



TECHNICAL DATA

Form	Paste
Color	White
Density	1.10 Kg/L
Working time	60 minutes
The solid residue	55%

CONSUMPTION

Depending on the type of used trowel:
200 - 400 g/m²

PACKAGING

DW RUBBER ECO 530 is supplied in buckets of 5 and 15 kg, in white color.

SHELF-LIFE-STORAGE

12 months if stored in a dry environment, in its original and unopened packaging.

