

DW SYNTHETIC ECO 220

Unit of measurement	Pieces/Pallet	Consumption	Color/Other specifications
5 kg/bucket	60 pcs/pallet	1-1.5 kg/m ²	Beige
15 kg/bucket	36 pcs/pallet		-



DW SYNTHETIC ECO 220

Polyurethane- based adhesive, for synthetic grass carpets.

CHARACTERISTICS

- DW SYNTHETIC ECO 220 is polyurethane- based, synthetic adhesive.
- DW SYNTHETIC ECO 220 is solvent-free.
- DW SYNTHETIC ECO 220 reaches a high level of flexibility and adhesiveness.
- DW SYNTHETIC ECO 220 ensures excellent adhesion in any type of support.
- DW SYNTHETIC ECO 220 ensures good workability even in low temperatures.

APPLICATION PROCEDURE

Preparation of the surface

The surface must be pre-prepared in accordance with technical requirements of sports fields' standards.

APPLICATION

Mix the adhesive before using it. If you see the formation of a superficial skin, remove it in any case. DW SYNTHETIC ECO 220 is applied on surfaces through a notched trowel, suitable for parquets. Working time of DW SYNTHETIC ECO 220 product is maximally 30 minutes in normal weather conditions and moisture level. If you see the creation of a skin during the application of DW SYNTHETIC ECO 220, the adhesive is removed and re-applied.

TECHNICAL DATA

Form	Paste
Color	Beige
Density	1.30 Kg/L
Working time	30 minutes
The solid residue	100%

CONSUMPTION

Depending on the type of trowel:

- 600-800 g/m² by using a 4 mm-notch trowel.
- 800 - 1000 g/m² by using a 6 mm-notch trowel.

PACKAGING

DW SYNTHETIC ECO 220 is supplied in buckets of 5 and 15 kg, in beige color.

SHELF-LIFE-STORAGE

12 months if stored in a cool environment, in its original and unopened packaging.

