

EPO DECOR 300

Unit of measurement	Pieces/Pallet	Consumption	Color/other specifications
1 kg/bucket	12 pcs/box	1:20	Transparent
5 kg/bucket	60 pcs/pallet	-	

EPO DECOR 300

Polyurethane-based decorative coat which serves for the treatment of decorative floors.

Product classification:

EPO DECOR 300 is classified according to EN 998 – 1 standard.

CHARACTERISTICS

For indoor and outdoor usage.

- High resistance to atmospheric conditions.
- Good workability.
- Forms a stable a long-lasting structure.

AREA OF APPLICATION

EPO DECOR 300 is suitable to create decorative layers with excellent waterproofing, adhesive and elastic qualities. It is used to create decorative layers on surfaces leveled with cement mortar.

APPLICATION PROCEDURE

Support preparation:

The support where EPO DECOR 300 will be applied should be cleaned beforehand from dirt and petroleum, oils, varnishes, wax residues and anti-adhesion materials. Cleaning of oils, varnishes, wax or anti-adhesion materials is done mechanically or manually. Before the application of EPO DECOR 300, the support should be leveled with the dried primer TECNOFIX. Supports should be flat and mechanically stable, in function of intended usage.



APPLICATION MANNER

EPO DECOR 300 is applied through a straight metallic screed directly to the surface treated beforehand with Resin PRIMER RE 1800 primer. After laying the product on the support, compact it through a metallic screed in order to create the surface we want.

TECHNICAL FEATURES

Form	Paste
Color	Various
Volumetric weight	1750 Kg/m ³
Application temperature	+5°C to +35°C

CONSUMPTION

5kg per meter square

SHELF-LIFE STORAGE

It is stored in its original, unopened packaging, protected by direct exposure to sun and frost, for at least 12 months after manufacture date.

