

FLATEX



Unit of measurement	Pieces/Pallet	Consumption	Color/other specifications
25 kg/sack	54 pcs/pallet	1.5 kg/m ² /mm	Grey



Cement-based, leveling mortar, for outdoor and indoor environments.

TECHNICAL FEATURES

- Cement-based mortar, with sand of selected granulometry and modified polymers.
- Serves to create a flat layer for the application of waterproofs and adhesives.

AREA OF APPLICATION

It is used to level indoor and outdoor supports, such as: to level pools before making them waterproof, and also other supports before the application of tile adhesives. During the product application, the temperature of the environment should be from +5°C up to +35°C.

SUPPORT PREPARATION

The support where the material will be applied should be dry, clean, uniform, absorbent and stable. There should not be external residues, such as: oils, varnishes, petroleum, etc.

MANNER OF PRODUCT APPLICATION

The product is applied manually through a screed. When the product is applied through a pump, be attentive about the consistency of the processing and do not mix it with other materials.



TECHNICAL DATA (AT 23°C AND 50% U.R)

Form	Powder
Color	Grey
Shelf-life storage	12 months in original packing in dry environments
Combustibility	incombustible
Density	1.4 kg/dm ³
Application temperature	from +5°C to +35°C
Opening time	>30 min
Support temperature	from +5°C to +25°C
Working temperature	from +5°C to +35°C
Trafficable	after 4-5 hours
The necessary time to pave the surface	≥ 2 days

FINAL DATA

Resistance to flexion (after 28 days) according to EN 1015-11	> 4 N/mm ²
Resistance to compression (after 28 days) according to EN 1015-11	> 35 N/mm ²

