

FLOORCOAT PAINT

Unit of measurement	Pieces/Pallet	Consumption	Color/other specifications
5 kg/bucket 10 kg/bucket	36 pcs/pallet 36 pcs/pallet	0.2-0.3 kg/m ²	White



FLOORCOAT PAINT

An acrylic-base resins in water dispersion paint, for marking indoor and outdoor sports fields.

FEATURES

An acrylic-base resins in water dispersion and filler-based of selected granulometry paint, for indoor and outdoor environments. Thanks to the formula of FLOORCOAT FINAL product, it has good coverage and longevity. The product has high resistance towards various weather conditions and towards abrasion. The product has excellent adhesive qualities in new surfaces and in pre-coated surfaces.

AREA OF APPLICATION

FLOORCOAT PAINT is used to coat sports floors, such as: tennis, basketball, volleyball, handball courts, tartar track in football pitches, etc.

MANNER OF APPLICATION

1. Surface preparation:

FLOORCOAT PAINT is applied on the dried surface where FLOORCOAT FINAL was applied beforehand, which serves for field's markings.

2. Product preparation:

FLOORCOAT PAINT can be diluted with 10% - 15% water and is stirred through a mixer which is suitable for homogenization. Then, the product is applied using a brush, roller or spray. The application of the product is made in two layers. The second layer is applied 12 - 24 hours after the application of first layer.

TECHNICAL FEATURES

Chemical base	Acrylic dispersion
Specific weight of mixture	1,50±0,05 kg/lit
Application temperature	From +10°C to +35°C
Recoat time	12-24 hours
Trafficable	About 24 hours according to the temperature

PACKAGING

In buckets of 5 kg and 10 kg.

CONSUMPTION

Smooth surface: 250 - 300 gr/m² / layer

SHELF-LIFE STORAGE

It is stored in a well-closed packaging, in dry, shady and low-moisture environments, for at least 12 months after manufacture date.

