

HYDRO PRIMER



Unit of measurement	Pieces/Pallet	Consumption	Color/other specifications
1 kg/plastic can	12 pcs/box	0.2-0.3 kg/m ²	Yellow
5 kg/plastic can	4pcs/box	-	-
10 kg/plastic can	60 pcs/pallet	-	-



DESCRIPTION

Elastomeric primer for surfaces where waterproof will be applied. Aqueous polymer dispersion is applied on porous surfaces thus by significantly increasing adhesiveness between elastomeric-based hydro isolators and support. HYDRO PRIMER has penetrating properties in all pores of the surface where waterproof will be applied, thus improving and enhancing the adhesive ability between the waterproof and the surface will be hydro-insulated.

AREA OF APPLICATION

HYDRO PRIMER is a ready to use PRIMER, which reinforces considerably waterproof adhesion on surfaces made of concrete, mortar, plaster and gypsum panels.

APPLICATION - CONSUMPTION

The surfaces to be treated with PRIMER should be completely dry and clean free of presence of dust. It is recommended to stir it before application. It is easily applicable with a brush or roller on surfaces, before the application of elastomeric waterproof.

Consumption: 200 - 300 g/m², depending on the porosity of the surface to be treated.

SHELF-LIFE STORAGE

The product can be stored for 18 months after manufacture date in its original packaging and in a dry place, at temperatures between +5°C to +35°C. You should avoid exposing the product at low temperatures (freezing) and high temperatures.

ATTENTION!

The product is recommended to be applied in the limits of temperatures from +5°C to +35°C

