

PARQUET AQUA LINE



| Unit of measurement | Pieces/Pallet | Consumption |
|---------------------|---------------|----------------------|
| Component A 1 kg | 12 pcs/box | 250 g/m ² |
| Component B 4 kg | 36 pcs/pallet | |



PARQUET AQUA LINE

Two component, polyurethane-based varnish, with high resistance to consumption, for extremely high-traffic floors.

FEATURES

Polyurethane-based varnish, for indoor and outdoor wood surfaces. Easily applied; manifests good elasticity and is laid in an excellent manner. It is particularly resistant to humidity and snow, while the UV filters it contains protect the wood from ultraviolet sun rays. Highlights and protects the natural beauty of all types of wood, accentuating their texture.

METHOD OF APPLICATION

1. Preparation of the surface

The right preparation ensures better results in new woods and old woods as well. A necessary condition is that the humidity of wood and atmosphere should be as low as possible. Before the application of PARQUET AQUA LINE, the surfaces must be rubbed with suitable sandpaper and they must be free of dust; if there is any resin, it must be removed. To preserve the natural wood color, 1 translucent, maintenance, coating layer is sufficient. To change the wood color, apply 1 translucent, maintenance layer and then 2-3 coloring layers. At the final stage, coat 1-2 layers with PARQUET AQUA LINE. If we are dealing with simple maintenance, a slight rubbing with sandpaper and the removal of dust is sufficient. In cases when old varnishes are in bad condition, they should be completely removed with a thick sandpaper. Having done that, follow the same procedure.

2. Application

PARQUET AQUA LINE, after mixing component A and B, is diluted up to 5% with white spirit. It is applied with brush, roller or pistol in 1-2 layers, depending on the application.

CLEANING

Clean the tools with white spirit

CONSUMPTION

1 lt/10-12 m² / layer, in well prepared surfaces.

SHELF-LIFE-STORAGE

It is stored in shady and dry environments, away from any heat source, for at least 24 months after manufacture date.

TECHNICAL DATA

| | |
|-------------------------|--|
| Color - Form | Transparent – Liquid varnish |
| Gloss | Satine, gloss |
| Drying time | 3-5 hours (to touch) depending on weather conditions |
| Re-coat | After 8-10 hours depending on weather conditions |
| Application temperature | From +5°C to +35°C |
| Specific weight | 0,90 ± 0,05 kg/lt |

