

PU 88 PRIMER

Unit of measurement	Pieces/Pallet	Consumption	Color/other specifications
1 kg/box	12 pcs/box	0.2-0.3 kg/m ²	1 kg
5 kg/box	4 pcs/box	-	5 kg
10 kg/box	60 pcs/pallet	-	10 kg



PU 88 PRIMER

Two component Polyurethane-Epoxy base primer.

DESCRIPTION

PU 88 Primer is a bi - component epoxy- based and water- based product. The product offers high physical and mechanical resistance, such as resistance to abrasion, resistance to water, acids, alkalis, petroleum products etc. It is used before the application of Izoelastich PU.

AREA OF APPLICATION

PU 88 PRIMER is used as a PRIMER when we use the product IZOELASTIC PU in waterproofing processes, in cases of terraces, etc.

INSTRUCTIONS FOR USE

The surface must be:

- Stable.
- Without the presence of materials that prevent connection, such as: dust, loose particles, grease, etc. Also, it must be prepared according to the nature of the surface. After this, the surface should be well cleaned from dust with a vacuum cleaner.

APPLICATION PROCEDURE

The product is ready for application and applied directly onto the floor surface through a roller or brush.

CONSUMPTION

300 gr/m² per layer

PACKAGING

It is supplied in metallic boxes of 5 Kg.

SHELF-LIFE STORAGE

12 months if stored in its original and unopened packaging, in dry places and in temperatures between 5°C - 25°C

